



. . . c o n n e c t i n g y o u r b u s i n e s s

LANCOM ES-1108P

8-port unmanaged 10/100 Mbps Fast Ethernet switch with four PoE ports

- 8-port unmanaged 10/100 Mbps Ethernet switch
- 4x Power over Ethernet compliant to IEEE 802.3af
- 15.4 W per PoE port possible
- Automatic detection of PoE devices and consumption
- Adapters for mounting in 19"-cabinets

Customised to support the LANCOM product portfolio, the LANCOM Ethernet Switch ES-1108P is the optimal component for structured cabling of home offices and smaller offices. Four power-over-Ethernet ports ensure maximum flexibility in positioning PoE-compliant VoIP telephones and access points.

All of the adapters necessary for mounting in 19" cabinets are supplied. This ensures that the LANCOM ES-1108P can be fully integrated into existing infrastructures.

LANCOM ES-1108P

| Standards | |
|--------------------------|---|
| Media | 10Base-T: UTP Cat. 3, 4, 5 or better 100Base-TX: UTP Cat. 5 or better |
| IEEE | IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX IEEE 802.3af |
| Operating modes | |
| Switching | Store and forward |
| Auto MDI/MDI-X | Yes |
| Transfer mode | 10/100 Mbps, full/half duplex (auto-sensing) |
| Transfer rate | 10 Mbps: 14.880 pps (64-byte packets) 100 Mbps: 148.800 pps (64-byte packets) |
| Flow control | IEEE 802.3x flow control in full-duplex mode Back-pressure flow control in half-duplex mode |
| Display | LEDs: Power, Link/Act, Speed, PoE activity |
| Hardware | |
| Power supply | 100V – 240V AC, internal power supply unit |
| Environment | Temperature range 0 – 40°C; humidity 5 – 90 %; non-condensing |
| Housing | Metal housing, connections on the front; measures 220 x 44 x 130.5 mm (W x H x D) |
| Power consumption (max.) | ca. 65 Watt |
| Weight | 1 kg |
| Approvals | |
| Conformity | CE conform with DIN EN 55022 and DIN EN 55024 |
| Package content | |
| Cable | IEC cable |
| Manual | Printed Quick Installation Guide (DE/EN) |
| Adapters | 19" adapters incl. mounting materials (two angles) |
| Item numbers | |
| LANCOM ES-1108P | 61450 |
| Service | |
| Warranty | 2 years |
| Support | Via hotline and Internet |
| Compability | |
| PoE feed (IEEE 802.3af) | <p>Compatible to: LANCOM L-54g Wireless LANCOM L-54ag Wireless LANCOM L-54dual Wireless LANCOM IAP-54 Wireless LANCOM XAP-40-2 LANCOM VP-100</p> <p>Hint Not suited for: LANCOM 3550 Wireless LANCOM OAP-54 Wireless*</p> |

* High-Power PoE-Injektor included

LANCOM, LANCOM Systems and LCOS are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. Subject to change without notice. No liability for technical errors and/or omissions.
02/07